



### New ways to use water



# Working with an internationally prestigious brand

In order to satisfy the continuous and growing demand of Laundry
Equipments, REALSTAR has founded a new division that take the name of AQUASTAR, that can supply a complete series of laundry for Industrial plant, Hospital, Hotels and Laundromat AQUASTAR is the perfect partner for professional carrying out comprehensive projects for global clients; a prestigious company offering quality products and competitive preand post-sales service.

# A solution for every customer

It doesn't matter how large or small your business is or what your requirements are: AQUASTAR can cater for them perfectly and provide you with a specific solution for every need.

We offer much more than just equipment sales: we offer all-round comprehensive Laundry Solutions.

Our range of washing, drying and ironing machines consists of state-of-the-art models designed for establishments of all kinds, from large hotel chains to small businesses, with a significant market presence in areas such as hospitals and health centres or coin laundry.

### Coin Laundry AQUASTAR

AQUASTAR can provide all types of machinery, accessories and consultation for one of the fastestgrowing areas of the industrial laundry sector, with a set of solutions guaranteeing the smooth functioning of any coin laundry installation, and our own systems for managing maintenance and payment processes. As regards payment processes, we have two systems to facilitate and automate the process: the basic coin operated washer extractor model (MA version) is designed for connection to a central payment unit, with no need for new or additional installations. For greater versatility, we have developed latest generation kits that can easily be mounted on the basic model, for instant adaptation of the washer extractor to fit an electronic coin/ token slot.

### **TOUCH SCREEN COMPUTER**



As a new feature in all ranges, we are presenting the TOUCH SCREEN COMPUTER, as well normal spin, fast spin and high spin washer extractor, which makes AQUASTAR range of washer, one of the widest in the market.



#### **TOUCH SCREEN**

Touch Screen of 4.3"

Programmer: 33 available languages.

USB port for washer's software updates and other application

Touch Screen Computer for OPL washer and coin washer



#### **PROGRAMMING**

User-friendly and intuitive programming.

26 pre-set program.

Possibility of programming, exporting and importing new programs (USB port)

Coin mode: a price can be assigned to each program



#### **FLEXIBILITY**

8 signals for automatic liquid dosing, programmable in time and delay

Delayed start, Timer (real time date)

3 standard water intakes

Configuration of washing and spinning speed

Complete regulation of water levels

Adjustable washing temperature from 20°C a 90°C

Standard WET CLEANING System

Main screen display and washing process, screen can be modified. with parameters and images suiting each client.

LOADING AID feature with water and rotation control for easy loading of the linen



#### **ENERGY EFFICIENCY**

4 Economic programs

REST mode, with automatic switch off.

Water recovery system, with double drain option. Water savings up to 70%.

OPTION: Automatic weighing system, up tp 30% savings. (automatic adjustment of water and soap consumption, as well as energy savings, according to the load which is automatically measured by the washer)

Optimal consumption standard. Manual indication of the load







### Reliable, robust and affordable

This range of washer extractors is specially designed and conceived for those markets and customers who look for a simple washer:

Hard-mounted, with **G Factor** of **200**, these models stand out for their energetic efficiency and low degree of detergents and water consumpton. It combines top-class features with a higher than-average performance, always geared to achieving greater energy efficiency during the wash, spin and dry processes.

This range of hard mounted machines – which require floor fixing – includes **25, 30, 40, 60, 80** and **130 lbs** capacity models.



- A skin platebody, more durable and hard-wearing than painted plate, and high quality components.
- Square structural pipe framework, highly resistant, prolonging the product's lifetime.
- Easier repairs, with alarms, statistics control, Memory, repair kits and a drum that can be removed via the front of the appliance, reducing the minimum space and time required.
- New detergent compartment with non-return system.
- Easy connection for automatic product dispensing.
- Automatic unbalance detection system enabling gentler movement and prolonging the components' lifetime.
- G factor of 200 on all models.
- Standard frequency inverter.





## HARD-MOUNTED machine type NEED anchoring to the floor



Model	Capacity	Extraction Speed	G Factor	Noise Level	Dimensions LxPxH mm	Net Weight
MAQ2 B 25	25 Lbs	759 r.p.m.	200	60 dB (A)	719 x 84 x 1158	Kg. 217
MAQ2 B 30	30 Lbs	759 r.p.m.	200	60 dB (A)	719 x 830 x 1158	Kg. 239
MAQ2 B 40	40 Lbs	714 r.p.m.	200	60 dB (A)	788 x 840 x 1307	Kg. 281
MAQ2 B 60	60 Lbs	682 r.p.m.	200	60 dB (A)	884 x 1011 x 1340	Kg. 340
MAQ2 B 80	80 Lbs	644 r.p.m.	200	60 dB (A)	979 x 1066 x 1411	Kg. 473
MAQ2 B 130	130 LBS	505 r.p.m.	150	60 dB (A)	1225 x 1279 x 1640	Kg. 930

Volume



	Series: MAQ2 B - TC								
		B 25	B 30	B 40	B 60	B 80	B 130		
DRUM									
Load Capacity	Lbs	25	30	40	60	80	130		
Drum Volume	Lt	100	130	180	250	350	600		
Basket diameter	Ø	620	620	700	770	860	1048		
Depth basket	mm	330	430	470	530	602	684		
Washing Speed	G/min	53	53	50	48	45	42,5		
Extraction Speed	G/min	538	538	507	483	458	416		
"G" Factor		200	200	200	200	200	150		
Noise Level	Db	60	60	60	60	60	60		
LOADING DOOR									
Height Center door	mm	570	570	655	700	735	900		
Door diameter	ø	373	373	373	373	560	560		
			I.	I.		I.			
POWER									
Motor power	Kw	0,75	1	1,5	2,2	3	5,5		
Electric Heating	Kw	6	9	12	18	21	28,8		
Total Power for ELECTRIC Version	Kw	6,25	9,3	12,5	18,75	22	31,3		
Total Power for STEAM Version	Kw	0,75	1	1,5	2,2	3	5,5		
Total Power for HOT WATER Version	Kw	0,75	1	1,5	2,2	3	5,5		
CONNECTIONS									
Drain water	Ø	3"	3"	3"	3"	3"	3"		
Water inlet	Ø	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"		
Water Pressure	Bar	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4		
Steam Inlet (only for STEAM Version	Ø	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"		
MACHINE DIMENSIONS									
Front Width	in	28.30	28.30	31.02	34.80	38.54	48.22		
Depth	in	26.18	31.89	32.60	37.99	41.97	50.39		
Height	in	45.59	45.59	51.50	51.89	55.43	64.57		
NET Weight	Lbs	478	527	620	750	1042	2050		
	<u> </u>								
MACHINE DIMENSIONS with PAGE Front Width	in	31.50	31.50	33.86	36.61	41.34	55.54		
Depth	in	38.98	38.98	39.76	46.46	49.21	57.48		
Height	in	53.15	53.15	59.05	61.42	62.99	74.02		
GROSS Weight	Lbs	496	544	664	816	1109	2315		

1,07

mt3

1,07

1,3

1,7

2,1

3,7